



busbar system, accessory busbar center-to-center spacing 60 mm busbar support
4-pole for busbars 12x 5 (10)-30x 5 (10) internal fixing width: 20 mm

Model	
product brand name	SENTRON
product designation	busbar support
operating voltage at AC rated value	690 V
suitability for use	Flat bars
type of connectable conductor cross-sections for copper conductor stranded	12 mm x 5 mm - 30 mm x 10 mm

Mechanical Design	
width	20 mm
busbar center-to-center spacing	60 mm

Approvals Certificates		
General Product Approval	Test Certificates	other



[Miscellaneous](#)

[Miscellaneous](#)

other	Environment
-------	-------------


[Confirmation](#)

[Environmental Con-
firmations](#)

[Environmental Con-
firmations](#)

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1923-4AA00>
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/8US1923-4AA00>
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1923-4AA00
CAx-Online-Generator
<http://www.siemens.com/cax>
Tender specifications
<http://www.siemens.com/specifications>



01485

last modified:

4/11/2025 

